



Depot (Title) OFS-03
 for (Quantity) LA Vendors
 of DG Class 3 and PG II and III
 as shown in this plan
 conforms with the Dangerous Goods Act 1975
 and Australian Standard(s) AS 1940 - 2017
 Signature: [Signature] Date: 6.9.18
 Name (printed): B. H. Baring 535
 LOADS SHOWN ARE
 LIMIT STATE LOADS

DETAIL AT HOLD-DOWN BOLTS

REF	MODEL	CAPACITY (l)	BUND VOL (l)	VENT AREA (m ²)	LENGTH "L" (m)	BUND DIMENSIONS	A	B	C	Fu	Fd	Fh
1	OFS-FNQ 3000	3000	949	0.21	2465	2285x2250x193	2	600	1285	48	60	48
2	OFS-FNQ 4800	4800	1423	0.32	3615	3415x2250x193	3	750	1058	69	89	69
3	OFS-FNQ 6700	6700	1897	0.42	4745	4545x2250x193	3	750	1082	92	117	90
4	OFS-FNQ 8600	8600	2371	0.52	5875	5675x2250x193	4	750	1458	113	144	111
5	OFS-FNQ 10000	10000	2844	0.63	7005	6805x2250x193	5	750	1376	134	174	134

UNLESS OTHERWISE STATED DIMENSIONS ARE IN mm

ENGINEERING DRAWING PRACTICE AS 1100 MATERIAL AND SPECIFICATIONS

FINISH

TOLERANCES UNLESS OTHERWISE STATED

SIZE RANGE	TOLERANCE
0 - 6	±0.2
6 - 50	±0.5
50 - 120	±0.7
120 - 300	±1
OVER 300	±2

DRAWN: [Signature] 27-10-88

CHECKED: _____

APPROVED: _____

PASSED: _____

SCALE: 1:20 AND 1:10

REFERENCE: AS1940-2004 of03-2005.dwg

TITLE: GENERAL ARRANGEMENT OFFS-FNQ FLAMMABLE LIQUID STORES

DRAWING N°: OFS-03

SHEET SIZE: A2

STORE-SAFE™

PART SECTION B-B (ALL ITEMS SYMMETRICAL ABOUT LONGITUDINAL C)

NOTES
 1. USE M20 CHEMSET OR HILTI TYPE HOLD-DOWN BOLTS AT LEAST 150 EMBEDMENT.
 2. STIFFENERS AND HOLD DOWN PLATES SUPPLIED BY STORE-SAFE
 3. BASE TO BE DESIGNED TO WITHSTAND THE WORST LOAD CASE SHOWN IN TABLE